


PRODUCT DATA


P R E M I U M[®] METAL-GUARD[®] VCI WIRE

Description



Extruded LDPE wire impregnated with Daubert Cromwell's multi-metal volatile corrosion inhibitors provides long-term corrosion protection in closed spaces. Clean, bendable Premium Metal-Guard VCI wire is typically used to prevent corrosion in closed tubing, pipes or conduits, linear motion devices, gun barrels and hard-to-reach areas of large equipment.

Features



Proven Daubert Cromwell corrosion inhibitor chemistry

- Protects a wide range of ferrous and non-ferrous metals.
- Odorless, non-toxic, recyclable.
- Safe and easy to use; no special handling required.
- Parts remain clean, dry and ready to use immediately without additional cleaning or rework.
- No residue or powder.
- RoHS compliant, OEM approved.
- Compatible with Daubert Cromwell rust preventive liquids, VCI papers, films, foams and emitters.
- Protects metal surfaces for up to 2 years, inside dry storage.



Typical Applications



For storage, transport, export of:

- Firearms and accessories. Barrels, spares, related equipment and attachments.
- Hollow, precision machined parts, linear parts and components.
- Long lengths of piping and metal tubing.
- Cylindrical parts and hollow void space up to 2" diameter.

Guidelines for use:

- Unroll and cut a length of wire equal to or slightly longer than length of tube, pipe or barrel.
- Place the wire in the tube. If desired, hook the wire around one end, for easy removal later. Seal or close ends of the hollow piece with wire inside.
- VCI will saturate the enclosed air space, protecting interior surfaces from corrosion until wire is removed.
- For other complex shapes and spaces, use: a) Daubrite[®] emitters (Daubrite 5 emitter protects 5 cu. ft. of space, Daubrite 10 for cu. ft.; b) Daubrite foam emitters; c) VCI chips or powder packets.



DAUBERT CROMWELL
The Leading Name in Corrosion Prevention[®]

12701 S. Ridgeway Ave | Alsip, IL 60803 USA | (800) 535-3535

Tel +1 (708) 293-7750 | E-mail: info@daubertcromwell.com | www.daubertcromwell.com



TECHNICAL DATA

PREMIUM METAL-GUARD® VCI WIRE

Physical Data

Typical Properties	Typical Values	
Outside diameter	1/8" (3mm)	
Inside diameter	1/10" (2.5mm)	
Form	Wire	
Color	Blue	
Protection Time		
Inside Dry Storage		Up to 24 months
Metal	Level of Protection	
Steel, AISI 1010	Protection	
Solder	Protection	
Brass, Red or White	Protection	
Bronze, including Naval	Protection	
Copper	Protection	
Stainless Steel, All Grades	Protection	
Zinc or White Metal	Protection	
Galvanized, hot dipped or electro galvanized	Protection	
Chromium and Chromium Plated	Protection	
Nickel and Nickel Plated	Protection	
Tinplate	Protection	

Storage

Store in a cool, dry place, away from direct sunlight. Do not store outdoors, in high humidity, or at temperature above 80°F (27°C).

Shelf Life

Two (2) years from date of shipping when stored in the original shipping container used by Daubert Cromwell and not in high humidity and not at high temperatures, or stored outside. Storage outside these conditions voids this statement.

WARRANTY The data, statements and recommendations in this product specification sheet are based on testing, research and other development work, which has been carefully conducted by us, and we believe such data, statements and recommendations will serve as reliable guidelines. Physical properties shown above represent typical values and are not intended for use in writing specifications. However, this product is subject to numerous uses under varying conditions over which we have no control, and accordingly, we do NOT warrant that this product is suitable for any particular use. Users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use. All products manufactured by us are warranted to be first class material and free from defects in material and

workmanship. Liability under this warranty is limited to the net purchase price of any such products proven defective or, at our option, to the repair or replacement of said products upon their return to us transportation prepaid. All claims on defective products must be made in writing within 30 days after the receipt of such products in your plant and prior to further processing or combining with other material and products. We make no warranty, express or implied, as to the suitability of any of our products for any particular use, and we shall not be subject to liability from any damages resulting from their use in operations not under our direct control. This warranty is exclusive of all other warranties, express or implied, and no representative of ours or any other person is authorized to assume for us any other liability in connection with the sale of our products.



DAUBERT CROMWELL
The Leading Name in Corrosion Prevention®

12701 S. Ridgeway Ave | Alsip, IL 60803 USA | (800) 535-3535
Tel +1 (708) 293-7750 | E-mail: info@daubertcromwell.com | www.daubertcromwell.com

Rev. JUL2019 SMD

